

MC type (dual moving coil) stereo cartridge

AT-ART2000 MC

(Tax removal XXYEN 55,000.) @ limitation 1,000 unit

It produced completed.



Western calendar 2000 age sense model



PCOCC6N

PCOCC=Pure Copper by Ohno Continuous Casting process
(Monocrystal condition high purity oxygen free copper) 6N=99.99996%

Compilation into one book of sound of 20 centuries which concentrate long time technology.

It did again to stare " the personality of analog "

Model of completeness.

- High intensity, you adopt the titanite acid kalium mixed resin which actualizes treble quality for VC mold which locks the coil.
- It traces the concave limits faithfully with the gold evaporation ボロンムク * tapered * cantilever. You produce the deep appearance impression.
- The PCOCC6N in the coil, adopting the PCOCC for the terminal pin, cleanliness transmission.
- You adopt the high magnetic force neodymium for the magnet. The treble quality which has the メリハリ.
- Are low distortion factor with the micro linear needle as many as approximately 1,000 hours high stability playback.
- In the base and inside the housing in the sound quality the profitable vibration-proof rubber " it leaps and employs the knight ".
- Screw for shell installation sound quality concern specification of brass make.
- Moisture absorption * water absorption characteristic is little, in the paulownia box whose Tsune hygroscopic is high the best condition keeping.

It continued to be loved in many analog fans in the world
Audio Technica cartridge.

2000 year in the turning point which is said hitting

Plan / the compilation into one book will be actualized, as for this model which is designed,
Sound quality preferential idea is meant in this corporation " the ART " (the Audio-technica Reference
Transducer) entitling
It was named " the ART2000 ".

This corporation chased after this model until now
" The advanced sound which is not defeated digitally exquisite balance of the analog sound quality /
advanced technology was included generously
After utilizing advanced quality as much as possible " to the maximum,
From " the personality which with only sound quality most preferential principle / analog is not obtained
" close-up.
The present analog user expects " personality of analog "
For the second time, doing again to stare, it makes and has been troubled.
Technology and know-how in order to reproduce analog unique deep sound carefully were included
generously
As for this model,
Those which you can be satisfied with everyone of the analog fan sufficiently we are convinced.

* Technical data

Type: MC (dual moving coil) type
Playback frequency range: 10 – 50,000Hz
Output voltage: 0.4mV (1kHz and 5cm/sec.
Channel * separation: 30dB (1kHz)
Output balance: 1dB (1kHz)
Stylus pressure: 1.6 – 2.0g (1.8g standard)
Coil * impedance: 12 Omega (1kHz)
Direct current resistance: 12 Omega
Load resistance: Head amplifier: 100 Omega or more
Trance: 20 Omega or more
Coil * inductance: 50 mu H (1kHz)

Static * compliance

35×10 – 6cm/dyne

Dynamic * compliance

9×10 – 6cm/dyne (100Hz)

Needle tip form: 0.1 Angular ML (micro linear) needle and ムクダイ
ア

Vertical tracking angle: 23°

External size: H17.3×W16.8×D25.7mm

Mass: 8.0g

Because (it is improvement and the like, there are times when it
modifies without notice.)

**– Needle exchange: The AT-ART2000 being to
become the limited commodity after production
end, (at needle exchange price to this corporation
suitable item) becomes exchange.**

Type turn	JAN cord/code	Carton	Package size	Sale day
AT-ART2000	T4961310036508	10PCS.	H122.5×W59×D114mm	November of 1999 21st

Back [Product information \(the cartridge & the audio accessory\) it returns to the home page](#)